

Yuvarlak Kesit Sıcak Çekme Üretim Toleransları EN 10060 (DIN 1013)

Round Shape - Hot Rolling Production Tolerances According To EN 10060 (DIN 1013)

www.kanatcelik.com



KANAT ÇELİK

SANAYİ VE TİCARET ANONİM ŞİRKETİ

EBAT Milimetre Milimeter (MM)	SAPMA SINIRI NORMAL TOLERANS Normal Tolerance (MM)	SAPMA SINIRI HASSAS TOLERANS (P) Tolerance (MM)	EBAT Milimetre Milimeter (MM)	SAPMA SINIRI NORMAL TOLERANS Normal Tolerance (Kg./m)	SAPMA SINIRI HASSAS TOLERANS (P) Tolerance (MM)	EBAT Milimetre Milimeter (MM)	SAPMA SINIRI NORMAL TOLERANS Normal Tolerance (Kg./m)	SAPMA SINIRI HASSAS TOLERANS (P) Tolerance (MM)
10	± 0.4	± 0.15	40	± 0.8	± 1.5	110	± 1.5	uygulanamaz / inapplicable
12			42		± 0.40	115		
14		± 0.20	45			120		
15			48			125		
16	± 0.5		50	130		± 2		
18			52	135				
19		55	140					
20		60	145					
22		63	150					
24		± 0.25	65	155				
25			70	160				
26			± 0.6	73	165		± 2.5	
27	75			170				
28	80	175						
30	85	180						
32	± 0.30	90		190				
35		95		200				
36		100	220	± 3				
38		± 0.8	105	± 1.5	250	± 4		